



AMFOR'S proprietary Microfiltration Series Spiral Element offer excellent performance in various applications.

**Element dimensions**

Element	Model Number	Diameter (Inches)	Length (Inches)	P.W.T.ID	Weight LB
<b>3.8"</b>	3838	3.8	38	0.83	10
	3839	3.8	39	0.83	10
	3850	3.8	50	0.83	13
	3851	3.8	51	0.83	14
<b>4.3"</b>	4333	4.3	33	0.83	11
	4335	4.3	35	0.83	11
	4336	4.3	36	0.83	11
	4336	4.3	36	0.83	11
	4338	4.3	38	0.83	12
	4350	4.3	50	0.83	15
	4351	4.3	51	0.83	15
4355	4.3	55	0.83	16	
<b>5.8"</b>	5838	5.8	38	1.14	15
<b>6.3"</b>	6338	6.3	38	1.14	16
	6356	6.3	56	1.14	24
<b>7.9"</b>	7940	7.9	40	1.14	38
<b>8"</b>	8038	8.0	38	1.14	38
	8238	8.2	38	1.14	40
	8338	8.3	38	1.14	42
<b>10"</b>	10338	10	38	1.14	45

**Element Area (aquare feet)**

Element	Model Number	Feed Spacer (in mils)				
		24	31	46	65	80
<b>3.8"</b>	3838	88	76	56	47	39
	3839	89	77	60	46	39
	3850	111	118	102	75	52
	3851	114	121	104	77	53
<b>4.3"</b>	4333	96	87	74	58	50
	4335	100	95	79	61	53
	4336	104	97	82	63	54
	4336	108	100	83	63	55
	4338	112	105	88	66	58
	4350	150	133	99	81	71
	4351	154	136	101	83	72
4355	166	147	109	90	78	
<b>5.8"</b>	5838	186	180	136	109	90
<b>6.3"</b>	6338	236	228	171	133	109
	6356	357	345	259	201	165
<b>8"</b>	8038	372	330	258	205	168
	8238	440	389	310	240	181
	8338	447	396	319	253	205
<b>10"</b>	10338	N/A	655	493	384	324

**Recommended element cross flow rate**

Element	Flow Unit	Feed Spacer(in mils)				
		24	31	46	65	80
<b>3.8"</b>	m3/h	6	6	7	9	10
	gpm	26	26	32	38	44
<b>4.3"</b>	m3/h	7	8	9	11	13
	gpm	32	34	42	49	59
<b>5.8"</b>	m3/h	13	14	17	20	23.1
	gpm	59	62	74	87	102
<b>6.3"</b>	m3/h	17	18	21	24	28
	gpm	75	78	93	106	123
<b>8"</b>	m3/h	26	27	32	37	43
	gpm	118	113	140	164	190
<b>10"</b>	m3/h	N/A	51	61	70	83
	gpm	N/A	224	268	307	366

Note: Not all combinations are available. For particular applications, please consult with us!